

Case ID:M21-029P^

Published: 4/23/2021

Inventors

Steven Wilson

Christopher Muhich

Ellen Stechel

Ivan Ermanoski

Contact

Shen Yan
shen.yan@skysonginnovations.
com

Doped Zeolite for Tunable Oxygen Separation and Pumping

Background

Oxygen (O₂) sorption materials can be used as a means for either producing a low partial pressure of oxygen (PO₂) environment for chemical processes or in the production of O₂ rich gas (>21 %) from leaner O₂ gas streams (O₂ composition < 21% down to PO₂ < 10 Pa or lower). Oxygen removal and O₂ enrichment are critical processes in many industrial applications, such as chemical looping, thermochemical fuel generation, partial oxidation processes such as of methane, and O₂ production. Current mechanical oxygen pumping equipment is energy intense and does not provide any separation properties.

Current O₂ separation techniques such as cryo-distillation have high cooling energy requirements and do not pump. A recent solution to these problems was the application of bulk materials for chemical-looping-based O₂ separation. These bulk materials, such as perovskites, require elevated operating temperatures (>250 °C) to facilitate oxygen exchange with the bulk. Although this has changed the energy form required to drive the process from electricity to heat, the high operating temperatures still incur a large thermodynamic energy penalty compared with operation at room temperature. As such, there is a need for materials to separate and pump O₂ with greater efficiency than traditional materials and processes.

Invention Description

Using high-surface-area porous materials and the sorption/desorption process, researchers at Arizona State University have developed doped zeolites to simultaneously separate and pump O₂. In the system, O₂ adsorbs to the zeolite even at low (1 Pa) pressures, separating the O₂ from the surrounding gas, if present. In the second pumping step, the temperature is increased, driving thermal O₂ desorption and thus regenerating the material to restart the cycle. The O₂ desorption pressure depends on the temperature, meaning that a higher final PO₂ can be achieved by increasing the desorption temperature. Conventional zeolites are incapable of performing this action as O₂ does not adsorb in its pores. However, zeolite O₂ adsorption is enabled by the inclusion of dopants (such as transition metals and semi-metals) with high-energy electron density. The number of dopant sites governs the pumping capacity, while dopant type can be used to engineer desired pumping strength—i.e., the lowest PO₂ from which O₂ can be extracted—and the temperature and PO₂ during release.

Potential Applications

- Oxygen removal and enrichment
- Chemical looping
- Partial oxidation of methane
- Solar hydrogen production

Benefits and Advantages

- Bypasses the high cost and inefficiencies associated with cryogenic distillation and mechanical alternatives
- Achieves oxygen adsorption at low pressures
- Requires much lower operating temperatures compared to perovskite methods
- Dopant selection allows tunability of operating temperatures, pressures, and pumping strength

Related Publication: [Substituted ALPO-5 Zeolites as Promising O₂ Sorption Pump Materials: A Density Functional Theory Study](#)

[Research Homepage of Professor Christopher Muhich](#)